



DMS International

320 Northpoint Parkway SE

Suite B

Acworth, Georgia 30102 USA

Tel: 770-529-6800

Fax: 770-529-6840

email: sales@dmsiusa.com

website: www.dmsiusa.com

JSC322-2 Twin Universal Ku LNBF

Specifications		
Input Frequency	10.7 – 11.7 Ghz	11.7 – 12.75 Ghz
Output Frequency	950 – 1950 MHz	1100 – 2150 MHz
LO Frequency	9.75 Ghz	10.6 Ghz
LO Initial Accuracy (@25°C)	± 1 MHz	
LO Temperature Drift (@ -40 – 60°C)	± 3 MHz	
LO Phase Noise	@ 1 KHz offset	-60 dBc/Hz
	@ 10 KHz offset	-80 dBc/Hz
	@ 100 KHz offset	-100 dBc/Hz
Noise Figure	0.3 dB or better (Typ.)	
Conversion Gain	60dB (Min.)	
Gain Variation (over operating band)	6dB p-p (Typ.)	
Gain Flatness (27 MHz)	±0.5 dB	
Cross Pol Isolation	25 dB (Min.) 25 dB (Typ.)	
Image Rejection	-50 dB (Min.)	
P 1dB	0 dBm (Min.)	
Output VSWR	2 : 1	
Spurious Response (@ 1700 MHz)	-58 dBm (Max.)	
DC Current Consumption	120 mA (Max.)	
Polarization Switching Voltage	Vertical: 10.5 – 14 V	
	Horizontal: 15.0 – 21 V	
Band Switching	Low: 0 KHz	
	High 22 ± 4 KHz	
LO Spurious	-45 dBm (Max.)	
Operation Temperature	-40°C to 60°C	
Waterproof	60°C water for 5 minutes	
Output Connector	75 ohm F type	